



Description

StarLite™ is an innovative LED bollard light which will enhance the aesthetic and accommodate the demands of different areas in entry-ways, building surround, parks, pathways, gardens and sidewalks.

Key Features

- IP66 and IK10
- Unique and elegant appearance
- Type IV / Type V light distribution

Applications

- Squares
- Gardens
- Parks
- Sidewalks

Electrical Information

Model No.	STL29-014	STL29-024
Power Consumption (±5%)	14W	24W
Power Supply	LIFUD / WELED Driver	
Input Voltage	120-277 VAC, 50 / 60 Hz	
Power Factor	>0.9	
Surge Protection	1kV line-line	
Driver Type	Constant Current (CC)	
Control	1-10V Dimming	

Optic Information

LED Type	LED 3030		
Luminous Flux (±5%)	1,260lm	2,160lm	
Efficacy(5000K Ra70)	90lm/W		
Correlated Color Temperature	4000K (3000K, 4000K optional)		
Color Rendering Index	Ra80		
Beam Angle	R03201(Type V) / R03202(Type IV)		
BUG rating	B2-U0-G1		

Dimensions

Product Dimension	φ165×500mm (φ6.5"×19.69")	φ165×900mm (φ6.5"×35.43")	φ165×500mm (φ6.5"×19.69")	φ165×900mm (φ6.5"×35.43")
Luminaire Net Weight	5.5±0.3kg (12.13±0.66Lbs)	7±0.3kg (15.43±0.66Lbs)	5.5±0.3kg (12.13±0.66Lbs)	7±0.3kg (15.43±0.66Lbs)
Export Carton Size				
Gross Weight				
Mounting Option	Mounting kit with anchor bolts			
Material	Corrosion Resistant Low Copper Aluminum Alloy Polycarbonate Optical Lens			
Finish	Electrostatically Applied Polyester Powder Coating			
Fixture Color	Black			
EPA	1.07	1.92	1.07	1.92
IK Rating	IK10			
IP Rating	IP66			

Lifespan and Warranty


Operating Temperature	-30°C to + 50°C(-22°F to 122°F)
Life Time of LED @Ta=25°C	36,000hrs-L90 70,000hrs-L80 150,000hrs-L70
Warranty	5 Years

New Features

**Please consult factory*


Photometry

Available in two optical asymmetric distributions.



Mounting Options

Mounting kit with anchor bolts




Accessories

HSS - House Side Shield



Dimensions

14W/24W



14W/24W

